

**Conduit Fittings For Over Braided Flexible Conduit, Fittings for heavy series flexible sheath**


( Straight Connector: **YABS**. 90 Degrees Connectors: **YALS**. 45 Degrees Connectors: **YAHS**)


All metal construction, heavy series Conduit Fittings are most suitable for **high temperature** wirings. Or with plastic sealing components for **liquid tight** applications. Metal clamping ring design provides **positive shielding termination**.

Most suitable for over braided flexible conduit and flexible metal conduit. Trade size: 1/4" - 6"  
Available with G, ISO228-1, Metric, PF; NPT or PG threads. **Male** or **Female** Threads




**Straight** Heavy Series Flexible Conduit Fittings


Straight Connector (fixed type)	Model	Size	0 degree Heavy Series Fixed	Model	Size
	YABS-02B	1/4"		YABS-20B	2"
	YABS-03B	3/8"		YABS-24B	2-1/2"
	YABS-04B	1/2"		YABS-30B	3"
	YABS-06B	3/4"		YABS-40B	4"
	YABS-10B	1"		YABS-50B	5"
	YABS-12B	1-1/4"		YABS-60B	6"
	YABS-14B	1-1/2"			

Straight Connector (swivel type)	Model	Size	0 degree Heavy Series Swivel	Model	Size
	YABSR-02B	1/4"		YABSR-14B	1-1/2"
	YABSR-03B	3/8"		YABSR-20B	2"
	YABSR-04B	1/2"		YABSR-24B	2-1/2"
	YABSR-06B	3/4"		YABSR-30B	3"
	YABSR-10B	1"		YABSR-40B	4"
	YABSR-12B	1-1/4"			


The external thread **swivels** about the main body. It can be used with threaded entries or knockout secured with a locknut. Most suitable for installations requiring **motion**, **vibration** and **bending**. Delikon heavy series **Swivel Connector** protects data or power cables of electric motor, blower, pump, polishing machine, grinding machine, or any other applications where there is vibration

### 90 Degrees Heavy Series Conduit Fittings

90 Degrees Connector (fixed type)	Model	Size	90 degrees Heavy Series Fixed	Model	Size
	YALS-03B	3/8"		YALS-14B	1-1/2"
	YALS-04B	1/2"		YALS-20B	2"
	YALS-06B	3/4"		YALS-24B	2-1/2"
	YALS-10B	1"		YALS-30B	3"
	YALS-12B	1-1/4"		YALS-40B	4"

90 Degrees Connector (swivel type)	Model	Size	90 degrees Heavy Series Swivel	Model	Size
	YALSR-03B	3/8"		YALSR-14B	1-1/2"
	YALSR-04B	1/2"		YALSR-20B	2"
	YALSR-06B	3/4"		YALSR-24B	2-1/2"
	YALSR-10B	1"		YALSR-30B	3"
	YALSR-12B	1-1/4"		YALSR-40B	4"

### 45 Degrees Heavy Series Conduit Fittings

45 Degrees Connector (fixed type)	Model	Size	45 degrees Heavy Series Fixed	Model	Size
	YAHS-02B	1/4"		YAHS-14B	1-1/2"
	YAHS-03B	3/8"		YAHS-20B	2"
	YAHS-04B	1/2"		YAHS-24B	2-1/2"
	YAHS-06B	3/4"		YAHS-30B	3"
	YAHS-10B	1"		YAHS-40B	4"
YAHS-12B	1-1/4"				

45 Degrees Connector (swivel type)	Model	Size	45 degrees Heavy Series Swivel	Model	Size
	YAHSR-02B	1/4"		YAHSR-14B	1-1/2"
	YAHSR-03B	3/8"		YAHSR-20B	2"
	YAHSR-04B	1/2"		YAHSR-24B	2-1/2"
	YAHSR-06B	3/4"		YAHSR-30B	3"
	YAHSR-10B	1"		YAHSR-40B	4"
YAHSR-12B	1-1/4"				

Delikon Heavy Series Over Braided Flexible Conduit, Heavy Series Braided Conduit Fittings protect servo, feedback motor cables, PLC cables, control cables, instrumentation cables. Reducing or eliminating electromagnetic interference (EMI) for cables. Delikon heavy series over braided flexible conduit and connector are particularly recommended for protecting supply cables between frequency converters and servo motors.

For the wiring of machines and system controls, Delikon heavy series braided conduit connector provides High Pull-Out Resistance, Robust Performance, Long Life Expectancy, Fastest and Easy installation.