



**Flexible Metallic Conduit ( YF-703 )**



DELIKON METAL LOCKED (SQ) FLEXIBLE METAL CONDUIT							
Type	Trade Size	I.D. (mm)		O.D. (mm)		Min. Bending Radius (mm)	Meter/Coil
		Min.	Max.	Min.	Max.		
YF-70301-SQ	-	7.8	8.2	10.8	11.2	25	100
YF-70302-SQ	1/4"	9.7	10.2	13.5	14.0	25	100
YF-70303-SQ	3/8"	12.3	12.8	15.3	15.8	35	50
YF-70304-SQ	1/2"	15.8	16.3	18.7	19.3	40	50
YF-70306-SQ	3/4"	20.8	21.3	23.7	24.2	45	50
YF-70310-SQ	1"	26.4	27.1	29.2	29.8	55	50
YF-70312-SQ	1-1/4"	35.0	35.8	37.7	38.3	60	30
YF-70314-SQ	1-1/2"	40.1	40.6	43.4	44.0	90	25
YF-70320-SQ	2"	51.3	51.9	54.8	55.4	110	20
YF-70324-SQ	2-1/2"	62.9	63.6	66.5	67.2	130	10
YF-70330-SQ	3"	77.9	78.7	81.6	82.4	155	10
YF-70340-SQ	4"	101.6	102.6	105.5	106.5	200	10
YF-70350-SQ	5"	125.0	127.0	135.0	137.5	250	5
YF-70360-SQ	6"	150.0	153.0	160.0	163.0	350	5



<b>DELIKON INTERLOCKED (IN) FLEXIBLE METAL CONDUIT</b> (HIGH TENSILE STRENGTH)							
Type	Trade Size	I.D. (mm)		O.D. (mm)		Min. Bending Radius (mm)	Meter/Coil
		Min.	Max.	Min.	Max.		
YF-70301-IN	-	<b>7.8</b>	8.2	<b>10.8</b>	11.2	25	100
YF-70302-IN	1/4"	<b>9.7</b>	10.2	<b>13.5</b>	14.0	25	100
YF-70303-IN	3/8"	<b>12.3</b>	12.8	<b>15.3</b>	15.8	35	50
YF-70304-IN	1/2"	<b>15.8</b>	16.3	<b>18.7</b>	19.3	40	50
YF-70306-IN	3/4"	<b>20.8</b>	21.3	<b>23.7</b>	24.2	45	50
YF-70310-IN	1"	<b>26.4</b>	27.1	<b>29.2</b>	29.8	55	50
YF-70312-IN	1-1/4"	<b>35.0</b>	35.8	<b>37.7</b>	38.3	60	30
YF-70314-IN	1-1/2"	<b>40.1</b>	40.6	<b>43.4</b>	44.0	90	25
YF-70320-IN	2"	<b>51.3</b>	51.9	<b>54.8</b>	55.4	110	20
YF-70324-IN	2-1/2"	<b>62.9</b>	63.6	<b>66.5</b>	67.2	130	10
YF-70330-IN	3"	<b>77.9</b>	78.7	<b>81.6</b>	82.4	155	10
YF-70340-IN	4"	<b>101.6</b>	102.6	<b>105.5</b>	106.5	200	10
YF-70350-IN	5"	<b>125.0</b>	127.0	<b>135.0</b>	137.5	250	5
YF-70360-IN	6"	<b>150.0</b>	153.0	<b>160.0</b>	163.0	350	5

**Flexible Galvanized Steel Conduit** is suitable for concealed, exposed, or approved raceways. The flexible conduit is manufactured with a spiral wound strip of corrosion and rust resistant, electro galvanized steel. The conduit features a smooth metal interior for easy wiring pulling. The flexible steel conduit is wire temperature rated, and has superior crush-proof qualities. *Delikon All Metal flexible conduit and conduit fittings are suitable for **Plenum** cable protection.*